

Attorney Docket No. 5725.0867
Customer No. OA 22,857

U.S. Reissue Application

of

U.S. Patent No. 6,089,410, issued July 18, 2000

Inventor:

Thierry Ponton

Title: PUMP-TYPE PACKAGING UNIT FOR A LIQUID
OR SEMI-LIQUID PRODUCT

0985720-10901
"02/28/60"

PUMP-TYPE PACKAGING UNIT FOR A LIQUID OR SEMI-LIQUID PRODUCT

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a unit for packaging and dispensing a liquid or semi-liquid product, of the type comprising a pump with manual action. The invention is especially suitable for packaging and spraying liquid products used in the field of cosmetics, or dermo-phannacology, such as perfumes.

2. Description of the Related Art

Devices for spraying liquids using a pump with manual action are well known. For example, FR 2 682 937 describes a pump-type spraying device comprising a pump mounted on a bottle and having a hollow stem which serves as an outlet conduit and as an actuating element, and is movable inside the body of the pump against the action of a spring. A dispensing cap is mounted on the bottle above the pump and has a pressurized actuating element provided with means for mechanical connection with the hollow stem. The cap also has a spraying nozzle and an internal duct which leads into the nozzle, as well as connecting means communicating the hollow stem with the internal duct of the cap. According to this document, the connecting means comprise a flexible tubular element joined to one end of the hollow stem and at the opposite end to the internal duct of the dispensing cap.

To dispense the product, the pressure actuating element is depressed, which produces the pump actuation and the emergence of the liquid through the outlet nozzle via the hollow stem, the flexible tubular element and the internal duct. Under the effect of the actuating pressure, the upper part of the cap carrying the nozzle yields at a connecting zone situated beneath the nozzle. The major drawback of such a device is due to the fact that the actuation of the pump produces a substantial modification of the position of the nozzle (by pivoting), which modification produces a change in the orientation of the sprayed liquid. Inevitably, if no precaution is taken, the product will not be sprayed to the desired spot. Another device of the same type, and hence with the same drawbacks, is described in EP-A 0 747 131.

In EP-A-0 385 077, the actuation of the pump produces an axial displacement of the outlet nozzle which must be taken into account with regard to the positioning of the spraying device relative to the surface to be treated, in the same way as the device discussed above, to ensure that the product is sprayed exactly to the desired spot. Moreover, such a design requires an oblong opening to be made opposite the nozzle, whose axial height depends on the amplitude of the axial movement of the nozzle. Such an opening of an elongate shape has a considerable effect on the aesthetic appearance of the device.

In another field, that is to say, the field of aerosols of the type comprising a pressurized container surmounted by a valve, it is known that the valve stem is connected via a conduit having a certain flexibility to an outlet opening that is substantially axially fixed, so as to absorb the axial displacement linked to the actuation of the pump as a whole, or in part. Such aerosol devices are described in FR-A 2 391 625, FR-A-2 271 995, FR-A-1 258 884, DE-A-2 655 777, U.S. Pat. Nos. 3,907,175, U.S. Pat. Nos. 3,189,232 and U.S. Pat. Nos. 5,1544,323. However, in the field of aerosols, the stroke necessary for actuating the valve is of the order of some hundredths of millimetres. In the case of a pump, the actuating stroke is of the order of several millimetres.

Typically, the actuating stroke is of the order of 6 to 7 mm. Thus the stresses to be taken into account for this type of technology have nothing to do with the stresses encountered in the aerosol devices. Because of this, for many of the devices described in these documents, the structure of the dispensing head would have to be completely thought out again to adapt it to the pump-type dispensing head, therefore requiring a considerable intellectual effort. Moreover, for certain products, perfumes in particular, it is desirable that they should not be packaged in a pressurized form.

SUMMARY OF THE INVENTION

Thus, one of the objects of the invention is to provide a device fitted with a pump for packaging and dispensing a product, in particular by spraying through an outlet element whose position is substantially fixed, in particular during the actuation of the pump.

Another object is to provide a pump-type device with an improved aesthetic appearance and which is simple and economic to obtain industrially.

In accordance with the invention, these and other objects are attained by creating a unit for packaging and dispensing a liquid or semi-liquid product, comprising a body with an axis X, forming a reservoir for the product, the reservoir being surmounted by a pump actuable by an actuating element, the product emerging through at least one opening arranged in an outlet element connected to the pump by a conduit forming a flexible connection, wherein the outlet element is held substantially immovably in position on a fixed portion of the body surmounting the reservoir, and the actuating element is independently mounted relative to the fixed portion of the body.

Thus, in accordance with the invention, the only connection between the outlet element and the movable actuating element is effected via a conduit forming a flexible connection. The flexibility of the connection absorbs substantially the whole of the movement of the said actuating element, so that during the actuation of the pump the outlet element is not substantially displaced.

Advantageously, the outlet element is a nozzle for spraying a liquid product such as a perfume. Such a nozzle has a known configuration and therefore does not require any detailed description.

According to a first embodiment, the body has a transverse partition separating a first space defining the reservoir from a second space surmounting the first, the second space containing the pump being mounted on an opening arranged in the partition, the actuating element mounted on the pump, the outlet element as well as the conduit forming the flexible connection.

Advantageously, the outlet nozzle is disposed substantially immovably at the bottom of a recess formed in a side wall of the second space, the recess opening out on a free edge of the second space situated opposite to the transverse partition. The hold in position of the nozzle immobile at the bottom of the recess (in particular its positioning perpendicular to the axis of the device) may be improved by providing inside the side wall an extra thickness in alignment with the bottom of the recess, which thickness increases the width of the support for the nozzle.

The outlet element may be mounted inside a housing communicating with the conduit forming the flexible connection, the actuating element, the housing as well as the flexible conduit forming a single part and being obtained by molding a thermoplastic material. By way of example, the thermoplastic material is a low density polyethylene (PEBD)

Such a protective element may have a body in the form of a rigid or semi-rigid annular part, the protective element being held in position on the end of the second space by means of an outer shell covering the unit substantially over its whole height, an opening being arranged in the external covering opposite the outlet element, the external covering having opposite the end of the second space a top with a cutout opposite the actuating element. Advantageously, locating pin-type marking means may be provided to permit a proper angular positioning of the shell relative to the rest of the body.

FIG. 1 is a view in perspective of a first embodiment of the packaging and dispensing unit according to the invention;

5

FIG. 2 is an exploded view of the unit shown in FIG. 1; FIGS. 3A and 3B are two sectional views of the embodiment of FIGS. 1 and 2; and

FIG. 4 shows a variant of the first embodiment shown in FIGS. 1, 2, and 3A-3B.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

As shown in an overall view in FIG. 1, the packaging and dispensing unit 1 takes the form of an upright cylinder entirely covered by an outer shell 2 of metal, such as aluminum or a thermoplastic material such as polypropylene. The outer shell covers the whole height of the device and has its bottom end open so as to allow the device itself to be inserted therein through the open end. The upper end is closed by a top 5 having a bevelled cutout 6 over a substantial part of its cross-section, from which there emerges a flexible portion of a protective element 7. The actuation of the device with a view to spraying the product is obtained by pressing via the flexible part on a push button contained inside the shell. An opening 8 is arranged on the shell opposite a nozzle 9 also contained inside the outer shell.

FIGS. 2 and 3A-3B illustrate a first embodiment of the device in detail. The device comprises a cylindrical body 10 comprising two parts 50, 51 separated by a transverse partition 11. The transverse partition delimits a bottom part 50 having a first space forming a reservoir 12 for the product to be dispensed. The top part 51 has a second space 13 containing all the elements necessary for dispensing the product, as will be seen in greater detail below.

The body is formed of a single piece obtained by molding (by injection molding for example) a material which is advantageously polyethylene terephthalate, for example. The bottom end 14 of the body 10 is obturated by an attached bottom 15. The attached bottom 15 has a first annular portion 17 whose external surface is provided with several beads or rings 18 capable of cooperating by catch engagement with corresponding beads arranged on the internal surface of the body 10 in the vicinity of its bottom end 14. The bottom 15 also has a second annular portion 19 capable of force fit engagement in the opening delimited by the free edge of the body 10. A part 16 with an external diameter substantially equal to the external diameter of the body 10 is situated beneath the annular portion 19 so as to limit the depression of the bottom 15 in the body. A groove 20 is disposed between the two annular portions 17, 19 so as to receive an O-ring 21 made of butyl in order to perfect the seal of the mounting of the bottom 15. The bottom 15 has a central opening 22 through which the reservoir 12 is filled after the attached bottom 15 has been mounted. Fins 23 are radially disposed in the space formed by the bottom 15 so as to stiffen its structure. The central opening is obturated by a stopper 24 comprising an axial part 25 with an external diameter substantially equal to the internal diameter of the opening 22 and a transverse side 26 with an external diameter substantially equal to the external diameter of the body 10. The stopper 24 is held in position in the opening by a force fit or by catch engagement. As will be seen more clearly in FIG. 2A, the stopper 24 defines, together with the attached bottom 15, an annular space 27 wherein an annular ballast (not shown) can be advantageously disposed.

The transverse partition 11 has a recess 28, in the bottom of which is arranged an opening 29 for the mounting of a pump 30. As will be clearly seen in FIGS. 3A and 3B, the recess 28 and the opening 29 are offset relative to the axis

6

X of the device and in a direction such that the axis of the pump 30 is a farther from the outlet nozzle 9 than is the axis X. The mounting of the pump in the recess 28 is advantageously obtained in the way described in detail in FR 2 669 244, that is to say, by means of an annular intermediate component 31, on the free edge of which the pump 30 is crimped. During the assembly, the pump 30 is first crimped onto the intermediate component 31. The unit is subsequently mounted by catch engagement in the recess 28 through the opening 29. A dip tube 32 dips into the reservoir 12, its free end being situated substantially in the vicinity of the bottom 15 of the reservoir.

The pump 30 has a hollow pump stem 33 whose free end emerges in the second space 13 delimited by the transverse partition 11. At its upper end 35, the free edge of the body 10 is straight over approximately one third of its section 36 (the front portion of the body) and cut out with a bevel over the rest of its section 37 (the rear part of the body). On the free end of the stem 33 there is mounted a push button 34 whose pressing surface 38 emerges from the cut out edge 37 and is situated substantially at the level of the straight edge 36. The push button 34 is disposed in a duct 39 which extends the upper part of the recess 28. The manual action pump is entirely conventional and therefore does not require any detailed description.

The duct 39 has a cutout 40 for passing a flexible conduit connecting an internal duct 52 arranged in the push button with an outlet nozzle 9 mounted in a housing 44 and held fixed in position at the bottom of a cutout 42 opening out on the straight edge portion 36 of the body 10. The cutout 42 is situated substantially opposite the cutout 40.

The conduit 41 has characteristics of suppleness, flexibility and elasticity which are such that the movement of actuating the push button does not produce any substantial movement of the outlet nozzle. In actual fact, due to the way in which the nozzle is mounted at the bottom of the cutout 42, there may occur a slight recoil or a slight rocking of the nozzle. However, these movements are hardly perceptible to the naked eye.

According to a preferred embodiment, the conduit 41, the housing 44 and the push button 34 are obtained by molding a single piece of low density polyethylene. In actual fact, only the pressing plate 38 is attached and mounted by catch engagement on the push button 34. The pressing plate is made of a more rigid material than the material constituting the rest of the push button. Advantageously, the pressing plate 38 is made of a high density polyethylene or polypropylene. The outlet nozzle 9 is formed of a piece of acetate mounted with a force fit in the housing 44.

As will be seen in FIG. 3B, the movement of actuating the push button 34 is reflected in an displacement of the flexible conduit 41, which displacement may be accompanied by an elongation of the conduit, particularly in the case of an elastomeric material or in the case of a bellows such as shown in FIG. 4. Since the housing 44 is also made of a flexible material, the end of the housing 44 adjacent to the conduit 41 may possibly slightly rock. On the other hand, the outlet nozzle situated in the front part of the housing 44 held tightly at the bottom of the cutout 42 is substantially immobile, which considerably facilitates the spraying of the product to the desired spot.

Other materials or arrangements may be used for obtaining the flexible connection between the push button 34 and the outlet nozzle 9. By way of example, the conduit 41 may be made of an elastomeric material (a sequenced copolymer of styrene-ethylene butadiene SEBS, EPDM). In the